

Technical Information

No. 5490

Edition: 01/09

Substitutes: Edition 01/08

Status: changed by MK 19.10.09

Xenon Short Arc Lamp

Xstage® 4000 W

■ Product description

The OSRAM Xstage® 4000 W is a DC-operated lamp that is especially suited for Entertainment applications requiring excellent arc stability and a high luminance.

■ Technical data

Order reference	Xstage® 4000 W	
Rated lamp wattage	W	4000
Rated lamp voltage	V	30
Rated lamp current (DC)	A	130
Current control range	A	80 - 135
Ignition voltage	kV _P	36
Min. open circuit voltage for cold / hot ignition	V	85 / 110
Luminous flux	lm	170000
Luminous intensity	cd	17000
Average luminance	cd/cm ²	120000
Luminous area w x h *)	mm	1,5 x 4,8
Electrode gap e (cold)	mm	6
Lamp length (overall) l ₁	mm	max. 320
Lamp length l ₂	mm	max. 277
LCL a	mm	120
Bulb diameter d	mm	60
Warranty (Stationary application) h	h	1000
Warranty (Moving application) h	h	650
Base	Cathode	SFc 28-27/20
	Anode	SFaX 27-9,5
Cable length l _c	mm	400

*) w = luminance half width value; h = height of luminous area (corresponds to electrode gap, hot)

■ Lamp operation

Maximum permissible base temperature	230°C
Cooling	forced cooling / fan
Min. air flow velocity around discharge vessel	7 m/s
Operating position	s90

