



product details

44892 SP

Product description: 44892 SP
 Product code: 4050300346182
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300346182

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326890
ILCOS	HRGS//UB-35-12-GU4-35/10

General Description	
Base (standard designation)	GU4
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage	35 W
Construction wattage	35 W
Nominal voltage	12 V

Technical - Geometries	
Overall length	42.00 mm
Contact spacing	4 mm
Diameter	35.0 mm
Length	40.00 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Luminous intensity	5000 cd
Beam angle	10 °
Color temperature	3000 K
Color rendering index Ra	100
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300346182	Folding carton box contains 1 Piece	38,000 mm x 34,000 mm x 50,000 mm	21,000 g (0,000 g)	0.065 Cubic dec.
4050300346199	Shipping carton box contains 10 Piece	183,000 mm x 58,000 mm x 81,000 mm	210,500 g (0,000 g)	0.836 Cubic dec.



product details

44892 SP

Every professional knows that light is not always the same when it comes to illuminating heat-sensitive objects. In this case the DECOSTAR 35 dichroic reflector lamp is the right choice because most of the heat produced by the lamp is emitted through the rear of the reflector. This reduces the heat in the light beam by up to 66 %. It is therefore easier to present heat-sensitive objects in the right light.

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 10 W - 2,900 K; 20 W/35 W - 3,000 K
- Base: GU4
- UV filter

For light distribution curves go to www.osram.com