

64341 HLX-Z/C 100-15

Halogen lamps, current-controlled with PK30d base



• Airfield lighting

Product benefits

- Reduced operation and maintenance costs due to long life time
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

Product features

• Dimmable

- $\boldsymbol{\cdot}$ Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions



Technical data


Electrical data	
Nominal voltage	15.2 V
Nominal wattage	100 W
Nominal current	6.60 A


Light technical data

Dimensions & weight

Diameter	13.5 mm
Length with base excl. base pins/connection	35.00 mm
Mounting length	16.0 mm
Light center length (LCL)	20.0 mm
Length	48.0 mm







Product line drawing

Base

Lifespan

Lifespan	1500 h	
Additional product data		
Base (standard designation)	PK30d	
apabilities		
	s90	

LIF	J1/79
Order reference	64341 HLX



Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.



Burning position



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4008321345653	Folding carton box 1	37 mm x 33 mm x 71 mm	20.50 g	0.09 dm ³
4008321345660	Shipping carton box 100	191 mm x 154 mm x 341 mm	2241.00 g	10.03 dm ³



References / Links

For more information on airfield lamps see the brochure: "The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.