

64635 HLX

Halogen lamps with reflector MR16



Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



Technical data

Electrical data


Nominal voltage	15 V
Nominal wattage	150 W

Light technical data

Focal length	19.0 mm

Dimensions & weight

Diameter	51.0 mm
Length	45.0 mm



Product line drawing

Product datasheet



Lifespan

Additional product data

Base (standard designation)	GZ6.35
Coating	Gold
Footnote used only for product	Infra-red lamp; temperature at the focal point approximately 1300 °C

Capabilities

Cooling	Forced
Burning position	hs30

Country specific categorizations

Order reference	64635 HLX

Product datasheet





Burning position



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300238807	Folding carton box 1	48 mm x 43 mm x 56 mm	34.00 g	0.12 dm ³
4050300946443	Shipping carton box 20	123 mm x 122 mm x 238 mm	836.00 g	3.57 dm ³



References / Links

For further technical information please refer to the following OSRAM brochure:

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

[&]quot;Technology and applications, Low-voltage tungsten-halogen lamps"

[&]quot;Halogen lamps, low and medium voltage for entertainment, technical and medical applications" cross reference list