

PRODUCT REQUIREMENT SHEET

See LV 075-031

MEASURING VOLTAGE	At rated voltage : 230 (stabilization 3 min)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal & Vertical
SWITCHING CYCLE	Continuous, twice daily OFF during 15 min
AGEING	1 hour at rated voltage

CHARACTERISTICS	VALUE	UNIT	TOL.	SPECIFICATIONS
WATTAGE	120	W	nom	+ 8%
	129,6		maxi	
LUMINOUS FLUX	2220	Lm	nom	Mini 90%
	1998		mini	
	1887		individual mini	
LUMEN MAINTENANCE AT 1500 h (AVERAGE)	85	%	mini	
LIFE TIME	50 % failure 2000	H	nom	under 230 V
	3 % failure 800		mini	
EFFICIENCY	18,5	lm/W		Indicative value
LAMP DIMENSIONS	78	mm	maxi	See 9299 994 1126x
PERMISSIBLE PINCH TEMPERATURE	350	°C	maxi	at 230 V
PERMISSIBLE BULB TEMPERATURE	900	°C	maxi	at 230 V
	250		mini	
WEIGHT	6,3	g		Indicative Value
ENERGIE EFFICIENCY LABEL (EEL)	D			
COLOR TEMPERATURE	2900	K		Indicative value



Remplace : Nouvelle	COMPACTE R7s	120 W 230 V	8233 120 44200	05/12/2014
REF:		CLEAR		SH 190-1
NOM : Éric SIRANTOINE	VALIDATION : J.M. WIHLIDAL		DOCUMENTATION DR. FISCHER PONT-A-MOUSSON	