

PRODUCT REQUIREMENT SHEET

See LV 075-031

MEASURING VOLTAGE	At rated voltage : 230 (stabilization 3 min)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal & Vertical
SWITCHING CYCLE	Continuous, twice daily OFF during 15 min
AGEING	1 hour at rated voltage

CHARACTERISTICS	VALUE	UNIT	TOL.	SPECIFICATIONS
WATTAGE	240	W	nom	+ 8%
	259,2		maxi	
LUMINOUS FLUX	4900	Lm	nom	Mini 90%
	4410		mini	
	4165		individual mini	
LUMEN MAINTENANCE AT 1500 h (AVERAGE)	85	%	mini	
LIFE TIME	50 % failure	H	2000	under 230 V
	3 % failure		800	
EFFICIENCY	20,4	lm/W		Indicative value
LAMP DIMENSIONS	118	mm	maxi	See 9299 994 1053x
PERMISSIBLE PINCH TEMPERATURE	350	°C	maxi	at 230 V
PERMISSIBLE BULB TEMPERATURE	900	°C	maxi	at 230 V
	250		mini	
WEIGHT	10	g		Indicative Value
ENERGIE EFFICIENCY LABEL (EEL)	D			
COLOR TEMPERATURE	2900	K		Indicative value



Remplace : Nouvelle	FLL R7s	240 W 230 V CLEAR	8238 240 44200	05/12/2014
				SH 190-1
REF:	VALIDATION : J.M. WIHLIDAL		DOCUMENTATION DR. FISCHER PONT-A-MOUSSON	
NOM : Éric SIRANTOINE				