



Capsuleline

Capsuleline 75W GY6.35 12V CL 4000h 1CT

Single-ended low-voltage halogen capsule giving crisp white halogen light. Compact shape, crisp white light. Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data

• General Characteristics

Philips Code	13101
Cap-Base	GY6.35
Cap-Base Information	15
Bulb	T4 [T4: .434 inch / 11mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Nominal Lifetime	4000 hr
Rated Lifetime (hours)	4000 hr
Rated Lifetime (years)	4 an

• Light Technical Characteristics

Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K
Luminous flux lamp	1400 Lm
Rated Luminous Flux	1400 Lm
Luminous Efficacy Lamp	18.8 Lm/W
LLMF - end nominal lifetime	80 (min) %

• Electrical Characteristics

Rated Wattage	75.0 W
Lamp Wattage	75 W
Lamp Wattage Technical	75.0 W
Power Factor	1 -
Voltage	12 V
Lamp Current	6.25 A
Dimmable	Yes

Starting Time	0.0 s
Warm-up Time to 60% Light Outp	instant full light

• Environmental Characteristics

Energy Efficiency Label (EEL)	C
Energy consumption kWh/1000h	80 kWh

• Measuring Conditions

Switching cycle	16000X
-----------------	--------

• Luminaire Design Requirements

Pinch Temperature	350 (max) C
Bulb Temperature	900 (max) C

• Product Dimensions

Overall Length C	44 (max) mm
Diameter D	12 (max) mm
Light Center Length L	30 mm

• Product Data

Order code	924040117101
Full product code	924040117101
Full product name	Capsuleline 75W GY6.35 12V CL 4000h 1CT
Order product name	Caps 75W GY6.35 12V CL 4000h 1CT/10X10F
Pieces per pack	1
Packing configuration	10X10F


PHILIPS

Capsuline

Packs per outerbox 100
Bar code on pack - EAN1 8711500402165
Bar code on intermediate packing - EAN2 8711500416995


Bar code on outerbox - EAN3 8711500425720
Logistic code(s) - 12NC 924040117101
ILCOS code HSG/C/UB-75-12-GY6.35
Net weight per piece 2.300 gr

Dimensional drawing



Capsuline 75W GY6.35 12V CL 4000h 1CT

Product	C (Max)	D (Max)	L (Norm)
CAP SU 13101 75W GY6.35 12V CL	44	12	30



GY6.35



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, November 5
data subject to change