

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal Free air burning
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	* ± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2450 K *2350 K ± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	94 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 526 44900			03/11/2015				
9245 526 44900		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		14132Z/98 235V 2000W REFL *													
Of 15/11/2010		DOCUMENTATION		UNIT	PROJ EUROPE	2	SH	SH	190-2	10			A4		
REF. : PDM IRK 2015-021				mm											
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															