

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	240V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	Horizontal
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

		VALUE UNIT	TOLERANCE
<b>WATTAGE</b>		1650W	± 6 %
<b>LIFE</b>		5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp HeLeN Lamp	2650 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	15500 lm 95 %	Indicative value min
<b>WEIGHT</b>		52 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 750 45500		02/11/2011					
9245 750 45500		INFRARED HeLeN						0833/000							
0833/000 p. 190-2		15048C 1650W 240V													
Of 16/12/2010		REF. : PDM IRK 2011-016		DOCUMENTATION		UNIT	mm	PROJ EUROPE	2	SH	SH	190-2	10		A4
NOM : PI120		VALIDATION : SN928						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															