

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Vertical
<b>BURNING POSITION</b>	Any
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE	
<b>WATTAGE</b>	2000W	± 6 %	
<b>LIFE</b>	5000 h	average	
<b>COLOR TEMPERATURE</b>	Clear lamp Lamp with reflector	2500 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	18000 lm 95 %	Indicative value min
<b>CAP INSULATION</b>	2000 V	mini	
<b>WEIGHT</b>	62 g		

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 802 44900			12/07/2012				
9245 802 44900		INFRARED HeLeN						0833/000							
0833/000 p. 190-2		15057Z 2000W 235V													
Of 17/12/2010		REF. : PDM IRK 2011-016		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10		A4			
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															