

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp HeLeN Lamp	2500 K NA	± 100 K
FLUX (HeLeN lamp) Clear lamp Reduction	18000 lm 95 %	Indicative value min
CAP INSULATION (WET)	2000 V	mini
WEIGHT	65 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 846 44900			13/07/2012				
9245 846 44900		INFRARED HeLeN						0833/000							
0833/000 p. 190-2		150083Z 1000W 235V													
Of 04/11/2010		REF. : PDM IRK 2011-016		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10		A4			
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															