

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	144V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		1200W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2400 K 2300 K	± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA	
WEIGHT		35 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 861 57700			16/07/2012				
9245 861 57700		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p. 190-2		13561U/98 1200W 144V REFL													
Of 12/01/2009		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															