

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	500W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2400 K 2300 K	± 100 K Indicative value
<b>FLUX (HeLeN lamp)</b>	NA	
<b>WEIGHT</b>	36 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 886 44900			14/04/2014				
9245 886 44900		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p.190-2		13169X/98 500W 235V X-CLIP REFL													
Of 02/02/2011		DOCUMENTATION		UNIT	PROJ EUROP	2	SH	SH	190-2	10			A4		
REF. : SLH/MS3/I1101				mm											
NOM : PI120		VALIDATION : SN928				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															