

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	1500W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp 2300 K Lamp with reflector NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	Clear lamp 10000 lm Reduction 95 %	Indicative value min
<b>CAP INSULATION (WET)</b>	2000 V	min
<b>WEIGHT</b>	47 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED HeLeN 15109A 1500W 235V						9245 938 44900			09/04/2013				
New								0833/000							
REF. :	MS2/I1233-30	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															