

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative value
FLUX (HeLeN lamp) Clear lamp Reduction	NA NA	
IRRADIANCE LEVEL	16000 W/m ²	Mini
WEIGHT	47 g	

Projet

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14243Z/83 2000W 400V REFL						9245 995 49100			27/06/2014				
New								0833/000							
REF. :	CRP 1418	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															