

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		2000W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp HeLeN Lamp	2500 K NA	± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	18000 lm 95 %	Indicative value min
CAP INSULATION (WET)		2000 V	mini
WEIGHT		60 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : New		HALOGEN LAMP INFRARED HeLeN 15140Z 2000W 235V						9246 147 44900 0833/000			05/10/2017				
REF. :	CRP 1745	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4				
NOM :	J.-J. FREY	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															