



MASTER TL5 High Efficiency Eco

MASTER TL5 HE Eco 19=21W/840 1SL

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HE Eco lamp offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Product data

• General Characteristics

Cap-Base	G5
Bulb	T5 [16 mm]
Life to 10% fail	21000 hr
Preheat EL,3h	
Life to 50% fail	25000 hr
Preheat EL,3h	
LSF HF Preheat	99 %
2000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	99 %
6000h Rated,3h	
LSF HF Preheat	99 %
8000h Rated,3h	
LSF HF Preheat	99 %
12000h Rated,3h	
LSF HF Preheat	99 %
16000h Rated,3h	
LSF HF Preheat	94 %
20000h Rated,3h	

• Light Technical Characteristics

Color Code	840 [CCT of 4000K]
Color Rendering Index	80 (min), 85 (nom), 85 (max) Ra8
Color Designation (text)	Cool White
Color Temperature	4000 K
Luminous Flux EL 25°C, Rated	1800 Lm
Luminous Flux EL 25°C, Nominal	1800 Lm
Luminous Flux Lamp EL 35°C	2100 Lm

Lum Efficacy Rated HF 25°C	96 Lm/W
Lum Efficacy Rated HF 35°C	112 Lm/W
LLMF HF 2000h Rated	96 %
LLMF HF 4000h Rated	95 %
LLMF HF 6000h Rated	94 %
LLMF HF 8000h Rated	93 %
LLMF HF 12000h Rated	92 %
LLMF HF 16000h Rated	91 %
LLMF HF 20000h Rated	90 %
Design Temperature	35 C
Chromaticity Coordinate X	380 -
Chromaticity Coordinate Y	380 -

• Electrical Characteristics

Lamp Wattage	19 W
Lamp Wattage EL 25°C, Rated	18.7 W
Lamp Wattage EL 25°C, Nominal	19.0 W
Lamp Wattage EL 35°C	18.7 W
Lamp Voltage EL 25°C	111 V
Lamp Voltage EL 35°C	111 V



asimpleswitch.com

PHILIPS

MASTER TL5 High Efficiency Eco

Lamp Current EL 25°C 0.170 A
 Lamp Current EL 35°C 0.170 A
 Dimmable Yes

• Environmental Characteristics

Energy Efficiency Label (EEL) A+
 Mercury (Hg) Content 1.4 mg
 Energy consumption kWh/1000h 21 kWh

• Measuring Conditions

Calibration Current 0.170 A
 HF Generator Rated Voltage 234 V
 Resistor 725 ohm

• Product Dimensions

Base Face to Base Face A 849.0 (max) mm

Insertion Length B 853.7 (min), 856.1 (max) mm
 Overall Length C 863.2 (max) mm
 Diameter D 17 (max) mm

• Product Data


Order code 927992484033
 Full product code 927992484033
 Full product name MASTER TL5 HE Eco 19=21W/840 1SL
 Order product name MASTER TL5 HE Eco 19=21W/840 1SL/40
 Pieces per pack 1
 Packing configuration 40
 Packs per outerbox 40
 Bar code on pack - EAN1 8727900918144
 Bar code on outerbox - EAN3 8718291224884
 Logistic code(s) - 12NC 927992484033
 ILCOS code FDH-19/40/1B-L/P-G5-16/850
 Net weight per piece 80.500 gr

Warnings and Safety

- A reduction in energy consumption is only achieved with current-controlled gear.


- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.

Dimensional drawing



MASTER TL5 HE Eco 19=21W/840 1SL

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL5 HE Eco 19=21W/840	849.0	853.7	856.1	863.2	17



G5

Photometric data



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, November 10
data subject to change