



TUV T8

TUV 15W SLV/25

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.


Product data

General Information		Voltage (Nom)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	54 V	
Main Application	Disinfection	Approval and Application	
Useful Life (Nom)	9000 h	Mercury (Hg) Content (Nom)	2.0 mg
System Description	-	UV	
Light Technical		UV-C Radiation at 100 hr	4.9 W
Color Code	TUV	Product Data	
Color Designation	- [Not Specified]	Full product code	871150072617940
Depreciation at Useful Lifetime	10 %	Order product name	TUV 15W SLV/25
Operating and Electrical		EAN/UPC - Product	8711500726179
Power (Nom)	15.9 W	Order code	928039004005
Lamp Current (Nom)	0.34 A	Numerator - Quantity Per Pack	1

TUV T8

Numerator - Packs per outer box	25
Material Nr. (12NC)	928039004005
Net Weight (Piece)	65.000 g



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TUV 15W SLV/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

TUV TL-D 15W

Photometric data



XDPB_XUTUVTLD-Spectral power distribution B/W

XDPO_XUTUVTLD-Spectral power distribution Colour

