

MASTERCcolour CDM-TT

MASTERCcolour CDM-TT 70W/942 E27 1SL

High-intensity discharge lamps with a CDM discharge tube inside a SON lamp clear tubular outer bulb



Product data

• General Characteristics

Cap-Base	E27
Bulb	T35 [T 35mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 5% failures	8000 hr
Life to 10% failures	10000 hr
Life to 20% failures	13000 hr
Life to 50% failures	18000 hr
LSF EM 2000h Rated, 12h cycle	99 %
LSF EM 4000h Rated, 12h cycle	99 %
LSF EM 6000h Rated, 12h cycle	97 %
LSF EM 8000h Rated, 12h cycle	95 %
LSF EM 12000h Rated, 12h cycle	82 %
LSF EM 16000h Rated, 12h cycle	62 %
LSF EM 20000h Rated, 12h cycle	37 %

• Light Technical Characteristics

Color Code	942 [CCT of 4200K]
Color Rendering Index	90 Ra8
Color Designation (text)	Cool White
Color Temperature	4200 K
Luminous Flux EM 25°C, Rated	6300 Lm
Lum Efficacy Rated EM 25°C	85 Lm/W

LLMF EM 2000h Rated	81 %
LLMF EM 4000h Rated	73 %
LLMF EM 6000h Rated	69 %
LLMF EM 8000h Rated	66 %
LLMF EM 12000h Rated	61 %
LLMF EM 16000h Rated	58 %
LLMF EM 20000h Rated	55 %
Chromaticity Coordinate X	379 -
Chromaticity Coordinate Y	375 -

• Electrical Characteristics

Lamp Wattage	70 W
Lamp Wattage EM 25°C, Nominal	70 W
Lamp Wattage EM 25°C, Rated	74 W
Lamp Voltage	91 V
Lamp Current EM	0.970 A
Ignition Time	30 (max) s
Run-up time 90%	4 (max) min
Dimmable	No
Re-ignition Time [sec]	720 (max) s
Ratio scotopic/photopic lumens	1.75 -

PHILIPS

MASTERColour CDM-TT

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	6.1 mg
Energy consumption kWh/1000h	81 kWh

• UV-related Characteristics

PET (NIOSH)	8 (min) h500lx
-------------	----------------

• Luminaire Design Requirements

Cap-Base Temperature	200 (max) C
Bulb Temperature	350 (max) C

• Product Dimensions

Overall Length C	156 (max) mm
Diameter D	36 (max) mm
Light Center Length L	102 mm

Arc Length O 6 mm

• Product Data


Order code	928093609235
Full product code	928093609235
Full product name	MASTERColour CDM-TT 70W/942 E27 1SL
Order product name	MASTERC CDM-TT 70W/942 E27 1SL/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500209658
Bar code on outerbox - EAN3	8711500209665
Logistic code(s) - 12NC	928093609235
ILCOS code	MT-70/942-H-E27-39/156
Net weight per piece	0.048 kg

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures

- Lamps may use electronic or electromagnetic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)

Dimensional drawing



MASTERColour CDM-TT 70W/942 E27 1SL


Product	C (Max)	D (Max)	L (Norm)	O (Norm)
CDM-TT 70W/942 E27	156	36	102	6

Dimensional drawing



E27

Photometric data



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, April 11
data subject to change