



MSD

MSD 200 1CT/40

These single ended, compact lamps enable optimal light collection and accurate beam control, while they also provide true daylight color temperatures – all to create great stage brightness and vivid entertainment. And since they offer long lifetime usage they help minimize the cost of ownership via fewer lamp replacements and fewer maintenance man hour costs.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information	
Cap-Base	GY9.5 [GY9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	2000 h
System Description	-
Light Technical	
Color Code	- [Not Specified]
Luminous Flux (Min)	11880 lm
Luminous Flux (Nom)	13200 lm
Chromaticity Coordinate X (Nom)	323
Chromaticity Coordinate Y (Nom)	328
Correlated Color Temperature (Nom)	6100 K
Luminous Efficacy (rated) (Nom)	66 lm/W
Color Rendering Index (Nom)	80

Operating and Electrical	
Power (Nom)	200 W
Lamp Current (Nom)	3.4 A
Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	-
Luminaire Design Requirements	
Bulb Temperature (Max)	500 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	872790091470200

Order product name	MSD 200 1CT/40
EAN/UPC - Product	8727900914702
Order code	928097205114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40

Material Nr. (12NC)	928097205114
Net Weight (Piece)	0.030 kg

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 200	23 mm	5.0	54 mm	56 mm	55	108 mm	29 mm	28	27 mm
1CT/40		mm			mm		mm		

MSD 200

Photometric data

