



MSR Gold™ FastFit

MSR Gold™ 700 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Correlated Color Temperature (Nom)		6000 K
Cap-Base	PGJX50 [PGJX50]	Luminous Efficacy (rated) (Nom)		71 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color Rendering Index (Nom)		80
Main Application	Entertainment	Operating and Electrical		
Life to 50% Failures (Nom)	750 h	Power (Nom)		700 W
System Description	FastFit	Lamp Current (Nom)		10.2 A
Light Technical		Ignition Supply Voltage (Min)		198 V
Luminous Flux (Min)	45500 lm	Controls and Dimming		
Luminous Flux (Nom)	50000 lm	Dimmable		Yes
Chromaticity Coordinate X (Nom)	327			
Chromaticity Coordinate Y (Nom)	336			

MSR Gold™ FastFit

Mechanical and Housing

Cap-Base Information PGJX50

Luminaire Design Requirements

Bulb Temperature (Max) 950 °C

Pinch Temperature (Max) 500 °C

Product Data

Full product code 871829122119700

Order product name MSR Gold™ 700 FastFit 1CT/4

EAN/UPC - Product 8718291221197

Order code 928106005115


Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 4

Material Nr. (12NC) 928106005115

Net Weight (Piece) 0.100 kg



Dimensional drawing



MSR GOLD 700 FastFit

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 700 FastFit 1CT/4	23.2 mm	3.8 mm	64 mm	66 mm	65 mm	112 mm	50 mm

Photometric data



XDPB_XDMSR_0001-Spectral power distribution B/W

