



# **MSR Gold™ FastFit**

## MSR Gold™ 2000/2 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR GoldTM FastFit can be operated in a lamp wattage range between 700W and 2500W.

#### Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### Product data

General Information				
Cap-Base	PGJX50 [ PGJX50]			
Operating Position	UNIVERSAL [ Any or Universal (U)]			
Main Application	Entertainment			
Life to 50% Failures (Nom)	750 h			
System Description	FastFit			
Light Technical				
Color Code	2			
Luminous Flux (Min)	138000 lm			
Luminous Flux (Nom)	160000 lm			
Chromaticity Coordinate X (Nom)	297			
·				

322
7500 K
80 lm/W
88
2000 W
15.4 A
198 V

Datasheet, 2020, March 19 data subject to change

## MSR Gold™ FastFit

Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Cap-Base Information	PGJX50			
Luminaire Design Requirements				
Bulb Temperature (Max)	950 ℃			
Pinch Temperature (Max)	500 ℃			
Product Data				
Full product code	872790090830500			

Order product name	MSR Gold™ 2000/2 FastFit 1CT/8
EAN/UPC - Product	8727900908305
Order code	928106105114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	928106105114
Net Weight (Piece)	0.147 kg

### Dimensional drawing



Product	D (max)	0	L (min)	L (max)	L	C (max)	F
MSR Gold™ 2000/2	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm
FastFit 1CT/8							

## MSR GOLD 2000/2 FastFit



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.