



# MSR Gold™ FastFit

## MSR Gold™ 2500/2 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

| General Information             |                                   | Operating and Electrical           |         |
|---------------------------------|-----------------------------------|------------------------------------|---------|
| Cap-Base                        | PGJX50 [ PGJX50]                  | Power (Nom)                        | 2500 W  |
| Operating Position              | UNIVERSAL [ Any or Universal (U)] | Lamp Current (Nom)                 | 19.53 A |
| Main Application                | Entertainment                     | Ignition Supply Voltage (Min)      | 198 V   |
| Life to 50% Failures (Nom)      | 750 h                             | Chromaticity Coordinate Y (Nom)    | 325     |
| System Description              | FastFit                           | Correlated Color Temperature (Nom) | 7200 K  |
| Light Technical                 |                                   | Luminous Efficacy (rated) (Nom)    | 77 lm/W |
| Color Code                      | 2                                 | Color Rendering Index (Nom)        | 85      |
| Luminous Flux (Min)             | 187500 lm                         |                                    |         |
| Luminous Flux (Nom)             | 193000 lm                         |                                    |         |
| Chromaticity Coordinate X (Nom) | 301                               |                                    |         |

# MSR Gold™ FastFit

## Controls and Dimming

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

## Mechanical and Housing

|                      |        |
|----------------------|--------|
| Cap-Base Information | PGJX50 |
|----------------------|--------|

## Luminaire Design Requirements

|                         |        |
|-------------------------|--------|
| Bulb Temperature (Max)  | 950 °C |
| Pinch Temperature (Max) | 500 °C |

## Product Data

|                   |                 |
|-------------------|-----------------|
| Full product code | 871829122131900 |
|-------------------|-----------------|

|                                 |                                |
|---------------------------------|--------------------------------|
| Order product name              | MSR Gold™ 2500/2 FastFit 1CT/4 |
| EAN/UPC - Product               | 8718291221319                  |
| Order code                      | 928106405115                   |
| Numerator - Quantity Per Pack   | 1                              |
| Numerator - Packs per outer box | 4                              |
| Material Nr. (12NC)             | 928106405115                   |
| Net Weight (Piece)              | 0.150 kg                       |



## Dimensional drawing



| Product                              | D (max) | O      | L (min) | L (max) | L       | C (max) | F     |
|--------------------------------------|---------|--------|---------|---------|---------|---------|-------|
| MSR Gold™<br>2500/2 FastFit<br>1CT/4 | 35.5 mm | 9.5 mm | 73.9 mm | 75.9 mm | 74.9 mm | 153 mm  | 50 mm |

## MSR GOLD 2500/2 FastFit

## Photometric data



XDPB\_XDMSR\_2500\_2\_FastFit-Spectral power distribution B/W

XDPO\_XDMSR\_2500\_2\_FastFit-Spectral power distribution Colour

