



MASTER SOX-E

MASTER SOX-E 18W BY22d 1SL

Low Pressure Sodium lamp with improved efficacy

Product data

• General Characteristics

Cap-Base	BY22d
Bulb	T50 [T 50mm]
Operating Position	h110 [Hanging +/-110D or Base Up (BU)]
Life to 5% failures	6000 hr
Life to 20% failures	12000 hr
Life to 50% failures	18000 hr

• Light Technical Characteristics

Color Temperature	1800 K
Luminous Flux Lamp EM	1800 Lm
Luminous Efficacy Lamp EM	100 Lm/W
Lumen Maintenance 2000h	95 %
Lumen Maintenance 5000h	90 %
Luminance Average EM	7 cd/cm ²

• Electrical Characteristics

Lamp Wattage	18 W
Lamp Wattage EM	18.0 W
Lamp Voltage	57 V
Lamp Current EM	0.33 A
Dimmable	No

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
-------------------------------	----

Mercury (Hg) Content	0 mg
Energy consumption kWh/1000h	20 kWh

• Luminaire Design Requirements

Cap-Base Temperature	150 (max) C
Bulb Temperature	150 (max) C

• Product Dimensions

Overall Length C	216 (max) mm
Diameter D	52 (max) mm

• Product Data

Order code	928145200008
Full product code	928145200008
Full product name	MASTER SOX-E 18W BY22d 1SL
Order product name	MASTER SOX-E 18W BY22d 1SL/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500192806
Bar code on outerbox - EAN3	8711500193407
Logistic code(s) - 12NC	928145200008
ILCOS code	LSE-E18-BY22d
Net weight per piece	0.150 kg

PHILIPS



Warnings and Safety

- Lamps may use electronic or electromagnetic control gear

Dimensional drawing

MASTER SOX-E 18W BY22d 1SL

Product	C (Max)	D (Max)
SOX E 18W BY22d T50	216	52



BY22d



© 2015 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, August 29
data subject to change