



# MSR Short Arc

## MSR 1200 SA 1CT/4

The lamp's short arc and compact design helps enable a compact luminaire that provides high beam intensity, while the excellent color rendition characteristics help ensure optimal colors on stage. The highly innovative P3 technology, developed by Philips, allows MSR Short Arc lamps to be used at higher temperatures in any burning position. The result? Longer lifetime, fewer early failures and a highly consistent performance throughout the lamp's lifetime.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information		Color Rendering Index (Nom)	
Cap-Base	GY22 [ GY22]		80
Operating Position	UNIVERSAL [ Any or Universal (U)]	Operating and Electrical	
Main Application	Studio/Disco	Power (Nom)	1200 W
Life to 50% Failures (Nom)	750 h	Lamp Current (Nom)	13.8 A
System Description	Short Arc	Ignition Supply Voltage (Min)	207 V
Light Technical		Controls and Dimming	
Color Code	- [ Not Specified]	Dimmable	No
Luminous Flux (Min)	86400 lm	Mechanical and Housing	
Luminous Flux (Nom)	96000 lm	Cap-Base Information	-
Chromaticity Coordinate X (Nom)	323	Luminaire Design Requirements	
Chromaticity Coordinate Y (Nom)	328	Bulb Temperature (Max)	1000 °C
Correlated Color Temperature (Nom)	6100 K		
Luminous Efficacy (rated) (Nom)	80 lm/W		

## MSR Short Arc

Pinch Temperature (Max)	500 °C
<b>Product Data</b>	
Full product code	871829122125800
Order product name	MSR 1200 SA 1CT/4
EAN/UPC - Product	8718291221258
Order code	928170905115

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928170905115
Net Weight (Piece)	0.096 kg


### Dimensional drawing



MSR 1200 SA

Product	D (max)	O	L (min)	L (max)	L	C (max)
MSR 1200 SA 1CT/4	34 mm	7.0 mm	58 mm	60 mm	59 mm	135 mm

### Photometric data



XDPB\_XDMSR\_SA-Spectral power distribution B/W

