MSR Gold™ FastFit

MSR Gold™ 2000 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR GoldTM FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

· A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	PGJX50 [PGJX50]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Entertainment
Life to 50% Failures (Nom)	750 h
System Description	FastFit

Light Technical	
Color Code	– [Not Specified]
Luminous Flux (Min)	162000 lm
Luminous Flux (Nom)	180000 lm
Chromaticity Coordinate X (Nom)	321

Chromaticity Coordinate Y (Nom)	332
Correlated Color Temperature (Nom)	6050 K
Luminous Efficacy (rated) (Nom)	90 lm/W
Color Rendering Index (Nom)	91

Operating and Electrical	
Power (Nom)	2000 W
Lamp Current (Nom)	15.2 A
Ignition Supply Voltage (Min)	198 V

data subject to change

MSR Gold™ FastFit

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Cap-Base Information	PGJX50

Luminaire Design Requirements

Bulb Temperature (Max)	950 ℃
Pinch Temperature (Max)	500 ℃

Product Data

Full product code	872790091949300

Order product name	MSR Gold™ 2000 FastFit 1CT/8
EAN/UPC – Product	8727900919493
Order code	928176905114
Numerator – Quantity Per Pack	1
Numerator – Packs per outer box	8
Material Nr. (12NC)	928176905114
Net Weight (Piece)	0.147 kg

Dimensional drawing

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 2000 FastFit 1CT/8	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm

MSR GOLD 2000W FastFit

www.lighting.philips.com

2020, March 19 – data subject to change