

# MASTER LEDspot LV

## MASTER LEDspotLV 4,5-20W 827 MR16 24D

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot and general lighting applications in the hospitality industry. It is particularly suited to public areas such as receptions, lobbies, corridors, stairwells and washrooms, where the light is on all the time. The robustly designed MASTER LEDspot offers a choice of beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

#### Product data

#### • General Characteristics

Cap-Base GU5.3

MR16 [MR 16inch/50mm] Bulb

Rated Lifetime 40000 hr

(hours)

Nominal Lifetime

40000 hr

#### • Light Technical Characteristics

Color Code Warm White

Color Designation (text)

24 D Beam Angle

2700 K Correlated Color

Temperature

207 Lm Luminous Flux Luminous Intensity 600 cd 80

Color rendering

index

Lamp

Luminous Efficacy 51.75 Lm/W

2700 K [CCT 2700K] Color Temperature Rated Luminous Flux

207 Lm LLMF - end nominal 70 %

lifetime

Colour consistency 6 steps Rated Beam Angle 24 D Luminous flux in 90° 207 Lm

## • Electrical Characteristics

Wattage 4 W Wattage Technical 4.5 W Voltage 12 V 50-60 Hz Line Frequency

0.7 -Power Factor Lamp Current mA 491 mA Nο Dimmable 20 W Wattage Equivalent Rated Wattage 4.5 W Starting Time 0.1 (max) s instant full light Warm-up Time to

60% Light Outp Suitable for accent

lighting

Yes

#### • Temperature Characteristics

#### • Environmental characteristics

**Energy Efficiency** Label (EEL)

#### Measuring Conditions

Switching cycle 50000X

#### • Product Dimensions

Overall Length C 50 mm 48.3 mm Diameter D

#### • Product Data

929000265102 Order code 929000265102 Full product code

MASTER LEDspotLV 4.5-20W 827 Full product name

MR16 24D

Order product name MAS LEDspotLV 4.5-20W 827 MR16

24D

Pieces per pack 1





# MASTER LEDspot LV

Packing configuration Packs per outerbox 10

10 8718291722366 Bar code on pack -EAN1 Bar code on 8718291722373

outerbox - EAN3

Logistic code(s) - 12NC 929000265102


0.060 kg Net weight per piece


# Warnings and Safety


 $\bullet$  Operating temperature range is between -20° C and 45° C ambient

- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

# Dimensional drawing







GU5.3

#### MASTER LEDspotLV 4.5-20W 827 MR16 24D

Product	C (Norm)	D (Norm)
LED 4.5-20W 827 MR16 24D	50	48.3



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.