



# Essential LEDspot GU10

## EcoBright LED GU10 50W 827 36D 2BC/5

Essential LEDspots are compatible with most existing fixtures with a GU10 socket and are designed as a retrofit replacement for halogen spots. Essential LEDspots deliver significant energy savings and minimize initial investment.

### Product data

General information	
Cap-Base	GU10 [ GU10]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	15000X
Technical Type	4.7-50W
Light technical	
Color Code	827 [ CCT of 2700K]
Beam Angle (Nom)	36 °
Luminous Flux (Nom)	400 lm
Luminous Intensity (Nom)	700 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	85.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	50 to 60 Hz

Power (Nom)	4.7 W
Lamp Current (Nom)	38 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.41
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	75 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb Shape	GU10
Approval and application	
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	5 kWh


# Essential LEDspot GU10

## Product data

Full product code	871869671774500
Order product name	EcoBright LED GU10 50W 827 36D 2BC/5
EAN/UPC - Product	8718696717752
Order code	929001250437
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	5
Material Nr. (12NC)	929001250437
Net Weight (Piece)	0.052 kg



## Dimensional drawing



EcoBright LED GU10 50W 827 36D 2BC/5


Product	D	C
EcoBright LED GU10 50W 827 36D 2BC/5	50 mm	54 mm

## Photometric data



LEDspot ESS 50W GU10 PAR16 827 36D ND



LEDspot ESS 50W GU10 PAR16 840 36D ND



LEDspot ESS 50W GU10 PAR16 827 36D ND

# Essential LEDspot GU10

## Lifetime



LEDspot ESS 50W GU10 PAR16 840 36D ND

LEDspot ESS 50W GU10 PAR16 840 36D ND

