



CorePro GLASS LED candles and lusters

CorePro LEDCandleND6.5-60W B35E14 865FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General information		Operating and electrical	
Cap-Base	E14 [E14]	Input Frequency	50 to 60 Hz
EU RoHS compliant	Yes	Power (Nom)	6.5 W
Nominal Lifetime (Nom)	15000 h	Lamp Current (Nom)	50 mA
Switching Cycle	20000X	Wattage Equivalent	60 W
Flux measurement reference	Sphere	Starting Time (Nom)	0.5 s
		Warm Up Time to 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.55
		Voltage (Nom)	220-240 V
Light technical		Temperature	
Color Code	865 [CCT of 6500K]	T-Case Maximum (Nom)	55 °C
Luminous Flux (Nom)	806 lm		
Color Designation	Cool Daylight	Controls and dimming	
Correlated Color Temperature (Nom)	6500 K	Dimmable	No
Luminous Efficacy (rated) (Nom)	124.00 lm/W		
Color Consistency	<6	Mechanical and housing	
Color Rendering Index (Nom)	80	Bulb Finish	Frosted
LLMF At End Of Nominal Lifetime (Nom)	70 %		

CorePro GLASS LED candles and lusters

Bulb Shape	B35 [B 35mm]
------------	---------------

Approval and application


Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	387445

Product data

Full product code	871951434754000
Order product name	CorePro LEDCandleND6.5-60W B35E14 865FRG

EAN/UPC - Product	8719514347540
Order code	929002028492
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002028492
Net Weight (Piece)	0.012 kg


Dimensional drawing




CorePro LEDCandleND6.5-60W B35E14 865FRG

Product	D	C
CorePro LEDCandleND6.5-60W B35E14 865FRG	35 mm	97 mm

Photometric data




LEDcandle E14 B35 865 FR



LEDbulb 6,5-60W E14 P45


CorePro GLASS LED candles and lusters

Photometric data




LEDbulb E14 P45

Lifetime



LEDbulb 6,5-60W E14 B35



LEDbulb 6,5-60W E14 B35

