

PHILIPS

Fortimo

LED

Fortimo LED Strip CES 2ft
2200lm LV5



Datasheet

A true Human Centric Lighting solution for office applications

Fortimo LED Strip CES 2ft 2200lm LV5 F

The impact of lighting on the human body is the subject of many research studies. Several studies have proven that the light spectrum influences the body's creation of the sleep hormone melatonin. In this area of human centric lighting (HCL) the Fortimo LED Strip CES HV/LV5 provides the right spectrum of light to help the human body to suppress the creation of melatonin during the day. This is being achieved by adding cyan light to the LED modules and combine them with white LEDs to create a neutral white color temperature. This technology is called Cyan Enhanced Static (CES) and is based on the Fortimo LED Strip platform. CES technology helps to achieve the highest MDER possible at a comfortable light quality.

Key features and benefits

- Upgrade your existing fixture easily to an HCL solution by applying Fortimo LED Strip CES
- MDER ≥ 0.86 possible at 500lux with comfortable light quality
- 4200K, CRI > 80, R9 >50
- Available in 1ft and 2ft
- Choose from high voltage or low voltage boards
- Highly efficient HCL solution: 161 lm/W
- Excellent color consistency of 3 SDCM
- Long lifetime solution: >70.000 hours
- Five years system warranty

October 2020



Ordering data

Commercial product name	EOC	12NC	Box quantity
Fortimo LED Strip CES 2ft 2200lm LV5 F	8718699 768218 00	9290 021 99106	84

Drive currents

Parameter	Nominal*	Life**	Max***	Unit
Fortimo LED Strip CES 2ft 2200lm LV5	500	1000	1200	mA

Module temperatures

Parameter	Nominal*	Life**	Max***	Unit
T _c (case temperature at T _c point)	45	70	85	°C

* Nominal value at which typical performance is specified

** Value at which life time is specified

*** Maximum value for safe operation, do not operate above this value

Optical characteristics - table per color (CCT)


Fortimo LED Strip CES 2ft 2200lm LV5 F

Parameter	Min	Typ	Max	Unit
Luminous flux	2090	2200	2310	lm
Module efficacy	152	161		lm/W
Correlated color temperature (CCT)		4200		K
Color coordinates (CIEx, CIEy)		(0.368, 0.360)		-
Color consistency			3	SDCM
CRI	80			
R9	50			
Photometric code		842/359		
Photobiological safety			RG1 unlimited	




Measurement precision for flux +/- 5%. Measurement precision for x, y +/- 0.005. Measurement precision for CRI 1.5

Operation point	842	lm	lm/W	
	Tc 25 °C		1805	165
80% I-nom 400mA	Tc-nom 45 °C		1782	163
	Tc-max 85 °C		1667	153
	Tc 25 °C		2226	163
I-nom 500mA	Tc-nom 45 °C		2200	161
	Tc-max 85 °C		2061	151
	Tc 25 °C		4957	151
I-max 1200mA	Tc-nom 45 °C		4899	150
	Tc-max 85 °C		4605	141



Beam shape

The module has a Lambertian light distribution



Electrical characteristics


Parameter	Min	Typ	Max	Unit
Forward voltage	27.3	27.3	28.4	V
Power consumption	13.7	13.7	14.2	W = kWh/1000h
Number of modules in series per chain			1	
Number of modules in parallel per chain			2	

Measurement precision for Vf +/- 3%. Measurement precision for power +/- 3.3%.

Tuning information


Flux and efficacy versus current (at Tc nominal)

I [mA]	Flux [%]	Efficacy [%]
1000	189	95
750	146	97
500	100	100
400	81	101
250	52	103



Flux and efficacy versus temperature at Tc (at I nominal)

Tc [°C]	Flux [%]	Efficacy [%]
70	97	97
45	100	100
25	101	101
0	102	102



Lumen maintenance


Operation point	Lumen maintenance x 1000 hours	L70			L80			L90		
		B50	B20	B10	B50	B20	B10	B50	B20	B10
80% I _{nom} 400mA	Tc 25°C	>70	>70	>70	>70	>70	>70	52	52	51
	Tc _{nom} 45°C	>70	>70	>70	>70	>70	>70	44	43	43
	Tc _{life} 70°C	>70	>70	>70	>70	>70	>70	38	38	38
I _{nom} 500 mA	Tc 25°C	>70	>70	>70	>70	>70	>70	52	52	51
	Tc _{nom} 45°C	>70	>70	>70	>70	>70	>70	44	43	43
	Tc _{life} 70°C	>70	>70	>70	>70	>70	>70	38	38	38
I _{life} 1000 mA	Tc 25°C	>70	>70	>70	>70	>70	>70	49	49	48
	Tc _{nom} 45°C	>70	>70	>70	>70	>70	>70	43	42	42
	Tc _{life} 70°C	>70	>70	>70	>70	>70	>70	36	35	35

Lifetime

Parameter	Value	Unit
M70F50 nominal	>70000	hours
M70F50 life	>70000	hours


Switching cycles in accordance to EU 1194/2012: >15000.

Performance Window



Wiring

Specification item	Value	Unit	Condition
Input wire cross-section	0.25...0.75	mm ²	solid wire
	18...24	AWG	solid wire
Input wire strip length	7.5...8.5	mm	
Input wire cross-section	0.33...0.5	mm ²	stranded wire
	20...22	AWG	stranded wire
Input wire strip length	7.5...8.5	mm	




More information in the design-in guide of LED Linear modules.



Mechanical characteristics

Parameter	Min	Typ	Max	Unit
Length	558.3	559.2	559.5	mm
Width	19.8	20	20.6	mm
Height PCB	1.44	1.6	1.76	mm
Height total		6.1		mm
Product mass		37		gram



Absolute ratings

Parameter	Min	Max	Unit
Current through the LED module (I-max)		1200	mA
Case temperature (Tc-max)		85	°C
ESD (direct contact)	8		kV
Working voltage		120	V _{dc}
Ambient temperature	-20		°C

Application information

Certificates and Standards

CE
 ENEC
 ENEC+
 UL

Environmental

RoHS/REACH

Application

Dimming	Yes
---------	-----



© 2020 Signify Holding, IBRS 10461, 5600VB, NL. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

www.philips.com/oem

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

01/10/2020