# Lighting

**PHILIPS** 

## MasterConnect LEDtube EM/mains T8

### MasterConnect LEDtube IA 600mm HO 7W865 T8 BR

Introducing MasterConnect LEDtubes – smart retrofit LED T8 lamps that give you an easy and seamless way to upgrade to connected lighting. Simply set up with an intuitive app and MasterConnect LED tube lighting can be programmed to maximize energy savings, while providing wireless and automated light for your comfort and convenience. What's more, it is fully scalable and upgradable. If you want to enjoy additional benefits such as remote control or a management dashboard, you can simply keep the lamps you currently have installed and add a gateway to experience all the advantages of a cloud-based system. There's no better way to take lighting solutions to the next level.

#### **Product data**

General information					
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]				
EU RoHS compliant	Yes 25000 h 200000X				
Nominal Lifetime (Nom)					
Switching Cycle					
Technical Type	7-18W				
Light technical					
Color Code	865 [ CCT of 6500K]				
Beam Angle (Nom)	160 °				
Luminous Flux (Nom)	1050 lm				
Color Designation	Cool Daylight				
Correlated Color Temperature (Nom)	6500 K				
Luminous Efficacy (rated) (Nom)	150.00 lm/W				


Color Consistency	<6				
Color Rendering Index (Nom)	83				
LLMF At End Of Nominal Lifetime (Nom) 70 %					
Operating and electrical					
Input Frequency	50 to 60 Hz				
Power (Nom)	7 W				
Lamp Current (Max)	37 mA				
Lamp Current (Min)	34 mA				
Starting Time (Nom)	0.5 s				
Warm Up Time to 60% Light (Nom)	0.5 s				
Power Factor (Nom)	0.92				
Voltage (Nom)	220-240 V				

#### MasterConnect LEDtube EM/mains T8


Temperature				
T-Ambient (Max)	45 ℃			
T-Ambient (Min)	-20 °C			
T-Storage (Max)	65 °C			
T-Storage (Min)	-40 °C			
T-Case Maximum (Nom)	40 °C			
Controls and dimming				
Dimmable	Wireless Dim			
Mechanical and housing				
Product Length	600 mm			
Bulb Shape	Tube, double-ended			
Approval and application				
Energy Saving Product	Yes			

Approval Marks	RoHS compliance CE marking KEMA Keur				
	certificate				
Energy Consumption kWh/1000 h	7 kWh				
Product data					
Full product code	871869973581400				
Order product name	MasterConnect LEDtube IA 600mm HO				
	7W865 T8 BR				
EAN/UPC - Product	8718699735814				
Order code	929002295412				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	10				
Material Nr. (12NC)	929002295412				
Net Weight (Piece)	0.115 kg				

#### Dimensional drawing



Product	D1	D2	A1	A2	A3
MasterConnect LEDtube IA	25.8 mm	28 mm	588.5 mm	595.5 mm	602.5 mm
600mm HO 7W865 T8 BR					




#### Photometric data




MC LEDtube 7W G13 1050lm 865

MC LEDtube G13 865


#### MasterConnect LEDtube EM/mains T8



#### Photometric data



#### MasterConnect LEDtube EM/mains T8



Life Expectancy Diagram

Lifetime



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, April 30 - data subject to change