



CorePro LEDlinear MV

CorePro LED linear R7S 78mm 4-40W 830 RCA

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General information	
Cap-Base	R7S [R7s]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	10000 h
Switching Cycle	5000X
Technical Type	4-40W
Light technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	475 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	118.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	4 W
Lamp Current (Nom)	20.5 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s


Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Ambient (Max)	35 °C
T-Ambient (Min)	-20 °C
T-Case Maximum (Nom)	100 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb Shape	Linear
Approval and application	
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	4 kWh
Product data	
Full product code	871869976148600
Order product name	CorePro LED linear R7S 78mm 4-40W 830 RCA

CorePro LEDlinear MV

EAN/UPC - Product	8718699761486
Order code	929002327087
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	929002327087
Net Weight (Piece)	0.008 kg



Dimensional drawing



Product	D	C
CorePro LED linear R7S 78mm 4-40W 830 RCA	14.5 mm	78 mm


CorePro LED linear R7S 78mm 4-40W 830 RCA

Photometric data



LEDlinear 4W R7S 830

LEDlinear R7S





© 2022 Philips Lighting B.V. Page 11

LEDlinear 4W R7S 830

CorePro LEDlinear MV

Lifetime



10K

10K

