



TrueForce Core LED Industrial and Retail (Highbay – HPI/SON/HPL)

TrueForce Core HB 65W E40 865 CN GN3


Philips TrueForce Core LED I&R lamps offer an easy and short payback LED solution to replace High Intensity Discharge (HID) lamps. The products bring the energy efficiency and long lifetime benefits of LED to HID replacement and provide instant saving and low initial investment. With the right lamp size and light distribution, you can easily retrofit TrueForce Core LED I&R lamps and bypass the existing ballast while enhancing the lighting quality.

Product data

General information		Color Consistency	
Cap-Base	E40 [E40]	Color Rendering Index (Nom)	80
EU RoHS compliant	Yes	LLMF At End Of Nominal Lifetime (Nom)	70 %
Nominal Lifetime (Nom)	25000 h	Operating and electrical	
Switching Cycle	50000X	Input Frequency	50 to 60 Hz
Light technical		Power (Nom)	65 W
Color Code	865 [CCT of 6500K]	Lamp Current (Nom)	540 mA
Beam Angle (Nom)	185 °	Wattage Equivalent	125 W
Luminous Flux (Nom)	7000 lm	Starting Time (Nom)	0.5 s
Color Designation	Cool Daylight	Warm Up Time to 60% Light (Nom)	0.5 s
Correlated Color Temperature (Nom)	6500 K	Power Factor (Nom)	0.5
Luminous Efficacy (rated) (Nom)	107.00 lm/W		


TrueForce Core LED Industrial and Retail (Highbay – HPI/SON/HPL)

Photometric data




LEDForce Core HB 65W Tshape E40 865

Lifetime



LEDspots LED 25K



LEDspots LMP 25K

