

# Other LEDtube



## LED 3.5W 500mm S14S WW ND 1CT/4

Philips LEDtube integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

### Product data

| General information                   |                     |
|---------------------------------------|---------------------|
| Cap-Base                              | S14S [ S14s]        |
| EU RoHS compliant                     | Yes                 |
| Nominal Lifetime (Nom)                | 30000 h             |
| Switching Cycle                       | 50000X              |
| Technical Type                        | 3.5-60W             |
| Flux measurement reference            | Sphere              |
| Light technical                       |                     |
| Color Code                            | 827 [ CCT of 2700K] |
| Beam Angle (Nom)                      | 140 °               |
| Luminous Flux (Nom)                   | 375 lm              |
| Color Designation                     | Warm White (WW)     |
| Correlated Color Temperature (Nom)    | 2700 K              |
| Luminous Efficacy (rated) (Nom)       | 107.00 lm/W         |
| Color Consistency                     | <6                  |
| Color Rendering Index (Nom)           | 80                  |
| LLMF At End Of Nominal Lifetime (Nom) | 70 %                |
| Operating and electrical              |                     |
| Input Frequency                       | 50 to 60 Hz         |
| Power (Nom)                           | 3.5 W               |
| Lamp Current (Nom)                    | 32 mA               |

| Starting Time (Nom)             | 0.5 s     |
|---------------------------------|-----------|
| Warm Up Time to 60% Light (Nom) | 0.5 s     |
| Power Factor (Nom)              | 0.4       |
| Voltage (Nom)                   | 220-240 V |
| Temperature                     |           |
| T-Ambient (Max)                 | 45 °C     |
| T-Ambient (Min)                 | -20 °C    |
| T-Storage (Max)                 | 65 °C     |
| T-Storage (Min)                 | -40 °C    |
| T-Case Maximum (Nom)            | 30 °C     |
| Controls and dimming            |           |
| Dimmable                        | No        |
| Mechanical and housing          |           |
| Bulb Finish                     | Frosted   |
| Bulb Material                   | Plastic   |
| Product Length                  | 500 mm    |
| Bulb Shape                      | Others    |
| Approval and application        |           |
| Energy Efficiency Class         | F         |

## Other LEDtube


|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| Energy Saving Product         | Yes                                              |
| Approval Marks                | RoHS compliance CE marking KEMA Keur certificate |
| Energy Consumption kWh/1000 h | 4 kWh                                            |
| EPREL Registration Number     | 387350                                           |

### Product data

|                    |                                 |
|--------------------|---------------------------------|
| Full product code  | 871951426358100                 |
| Order product name | LED 3.5W 500mm S14S WW ND 1CT/4 |

|                                 |               |
|---------------------------------|---------------|
| EAN/UPC - Product               | 8719514263581 |
| Order code                      | 929002444301  |
| Numerator - Quantity Per Pack   | 1             |
| Numerator - Packs per outer box | 4             |
| Material Nr. (12NC)             | 929002444301  |
| Net Weight (Piece)              | 0.140 kg      |


## Dimensional drawing




LED 3.5W 500mm S14S WW ND 1CT/4

| Product                         | D1    | D2    | A1       | A2 | A3     |
|---------------------------------|-------|-------|----------|----|--------|
| LED 3.5W 500mm S14S WW ND 1CT/4 | 30 mm | 30 mm | 466.8 mm |    | 499 mm |

## Photometric data




LEDtube 3,5W S14S 375lm 827



LEDtube 2,2W S14S 250lm 827


# Other LEDtube

## Photometric data




LEDtube 2,2W S14S 250lm

## Lifetime




Life Expectancy Diagram



LEDtube 30K LifetimeVsTc


LEDtube 30K FailureRate



Lumen Maintenance Diagram

## Other LEDtube

### Lifetime



LEDtube S14 30K LumenVsTc

