



MasterConnect T8

14.5T8/48-835/MF20/MC IA 10/1

Introducing MasterConnect LED lamps - smart retrofit LED lamps that give you an easy and seamless way to upgrade to connected lighting. Simply set up with an intuitive app, MasterConnect LED lamps can be programmed to maximize energy savings, while providing wireless and automated light for your comfort and convenience. What's more, it is fully scalable and upgradable. If you want to enjoy further benefits such as remote control or management dashboard, you can simply keep the currently installed lamps and add a gateway to experience all the advantages of a cloud-based system. There's no better way to take lighting solutions to the next level.

Product data

General information		LLMF At End Of Nominal Lifetime (Nom) 70 %	
Cap-Base	G13 ROT (Rotating) [Medium Bi-Pin Fluorescent]	Operating and electrical	
EU RoHS compliant	Yes	Input Frequency	50 to 60 Hz
Nominal Lifetime (Nom)	70000 h	Power (Nom)	14.5 W
Switching Cycle	50000X	Lamp Current (Max)	125 mA
Technical Type	14.5-25-28-30-32W	Lamp Current (Min)	59 mA
Light technical		Wattage Equivalent	25-28-30-32 W
Color Code	835 [CCT of 3500K]	Starting Time (Nom)	1 s
Beam Angle (Nom)	160 °	Warm Up Time to 60% Light (Nom)	0.5 s
Luminous Flux (Nom)	2000 lm	UL Type	TLED_Type B; UL classified double end
Color Designation	White (WH)	Power Factor (Nom)	0.9
Correlated Color Temperature (Nom)	3500 K	Voltage (Nom)	120-277 V
Luminous Efficacy (rated) (Nom)	137.00 lm/W	Temperature	
Color Consistency	<6	T-Ambient (Max)	45 °C
Color Rendering Index (Nom)	82	T-Ambient (Min)	-20 °C
		T-Storage (Max)	65 °C

MasterConnect T8

T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	45 °C

Controls and dimming

Dimmable	Wireless Dim
----------	--------------

Mechanical and housing

Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	1200 mm
Bulb Shape	Tube, double-ended

Approval and application


Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate DLC compliance

Energy Consumption kWh/1000 h	- kWh
-------------------------------	-------

Product data

Order product name	14.5T8/48-835/MF20/MC IA 10/1
EAN/UPC - Product	046677562731
Order code	929002456604
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002456604
Net Weight (Piece)	0.220 kg
Model Number	9290024566


Dimensional drawing




14.5T8/48-835/MF20/MC IA 10/1

Product	D1	D2	A1	A2	A3
14.5T8/48-835/MF20/MC IA 10/1	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm

Photometric data




LEDtube MAS 14,5W G13 2000lm 835



LEDtube MAS 14,5W G13 2100lm



Photometric data



© 2022 Philips Lighting B.V. Page 10 of 11


LEDtube MAS 14,5W G13 2000lm 835

Lifetime



LEDtube 14,5W 70K LumenVsTc

LEDtube_70K-LED



LEDtube_70K_LifetimeVsTc-LED

LEDtube_70K_FailureRate-LED

MasterConnect T8

Lifetime



LEDtube_70K-LMP

