



# **MASTER LED Strip**

## Master LEDstrip 21.3W965 2450LM/M 5M

A complete family delivering superior light with great uniformity and safety. Choose the best fit for every projects, from 5 lumen packs/wattages, and 4 CCTs, and enjoy great reliable performance free of maintenance

## **Product data**

General information	
Driver included	No
Control interface	depends on driver (1-10V, DALI)
Cable	Cable 0.3 m without plug
Protection class IEC	Safety class III
Glow-wire test	Temperature 650 °C, duration 30 s
CE mark	CE mark
Warranty period	5 years
Constant light output	Yes
Number of products on MCB of 16 A type B	-
EU RoHS compliant	Yes
Operating and electrical	
Input Voltage	24 V
Initial CLO power consumption	81 W
Average CLO power consumption	0 W
Power Factor (Min)	1
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Reflector material	-
Overall length	5000 mm

Overall width	8 mm	
Overall height	1.3 mm	
Approval and application		
Ingress protection code	IP20 [ Finger-protected]	
Mech. impact protection code	IK00 [ No protection]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	0 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	115.00 lm/W	
Init. Corr. Color Temperature	6500 K	
Init. Color Rendering Index	80	
Initial chromaticity	(0.3090, 0.3230) 3SDCM	
Initial input power	81 W	
Power consumption tolerance	+/-10%	
Over time performance (IEC compliant)		
Median useful life L70B50	60000 h	
Application conditions		
Ambient temperature range	-20 to +40 °C	
Maximum dim level	10% (depends on dimmer, ELV)	

Datasheet, 2022, March 7 data subject to change

## **MASTER LED Strip**

Product data	
Full product code	871951434470900
Order product name	Master LEDstrip 21.3W965 2450LM/M 5M
EAN/UPC - Product	8719514344709
Order code	929002698202
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	10
Material Nr. (12NC)	929002698202
Net Weight (Piece)	0.100 kg





## Dimensional drawing



### Master LEDstrip 21.3W965 2450LM/M 5M

### Photometric data





Calval XX Procongrador 6.2.2 Polito Listerior EXX Proc 92

MAS LEDstrip 21,3W 965 2450LM 5M-LDD

MAS LEDstrip 21,3W 965 2450LM 5M-GUL



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.