



UltraEfficient LED bulb

MAS LEDCandleND2.3-40W E14 830B35 CLG UE

This is the most efficient LED bulb from Signify. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

Product data

General information	
Cap-Base	E14 [E14]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
Flux measurement reference	Sphere

Light technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	485 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	210.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	2.3 W

Lamp Current (Nom)	30 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.35
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	70 °C

Controls and dimming	
Dimmable	No

Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	B35 [B 35mm]


Approval and application	
Energy Efficiency Class	A
Energy Consumption kWh/1000 h	3 kWh

UltraEfficient LED bulb

EPREL Registration Number	1099138
Product data	
Full product code	871951443595700
Order product name	MAS LEDCandleND2.3-40W E14 830B35 CLG UE
EAN/UPC - Product	8719514435957

Order code	929003480802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929003480802
Net Weight (Piece)	0.030 kg


Dimensional drawing




MAS LEDCandleND2.3-40W E14 830B35 CLG UE

Product	D	C
MAS LEDCandleND2.3-40W E14 830B35 CLG UE	35 mm	125 mm


Photometric data



Spectral Power Distribution Colour




Light Distribution Diagram



General uniform lighting

UltraEfficient LED bulb

Lifetime



50K

50K

