



PL-S Blacklight Blue

PL-S 9W BLB/2P 1CT/6X10CC

PL-S Blacklight Blue is a special low-wattage compact fluorescent lamp emitting long wave UV radiation for detection and analysis purposes in archaeology, money checking, forensic science, food industry, medicine, mineralogy, philately as well for special effects in night clubs, discos, theatres and sign lighting. The 2-pin version is designed for operation on electromagnetic gear, the 4-pin version is designed for operation on electronic gear. Both versions are provided with a plug-in/pull-out lamp base.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		
General Information		
Cap-Base	G23 [G23]	
Main Application	Blacklight Blue	
Useful Life (Nom)	3000 h	
Light technical		
Color Code	108 [08 lead free glass]	
	Blacklight Blue	
Color Designation	Blacklight Blue	
Color Designation LLMF 2000 h Rated	Blacklight Blue 20 %	
LLMF 2000 h Rated	20 %	
LLMF 2000 h Rated	20 %	
LLMF 2000 h Rated LLMF 6000 h Rated	20 %	
LLMF 2000 h Rated LLMF 6000 h Rated Operating and electrical	20 %	

Voltage (Nom)	60 V	
Mechanical and housing		
Cap-Base Information	2 Pins	
Bulb Shape	2XT12	
Approval and application		
Mercury (Hg) Content (Nom)	3.0 mg	
UV		
UV-B/UV-A (IEC)	0.2 %	
UV-A Radiation 100Hr (IEC)	1.65 W	
Product data		
Full product code	871150095090180	


Datasheet, 2022, January 14 data subject to change

PL-S Blacklight Blue

Order product name	PL-S 9W BLB/2P 1CT/6X10CC	
EAN/UPC - Product	8711500950901	
Order code	927901710807	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	60	

Material Nr. (12NC)	927901710807
Net Weight (Piece)	32.000 g

Dimensional drawing



PL-S 9W BLB/2P 1CT/6X10CC

Product	D1 (max)	B (max)
PL-S 9W BLB/2P 1CT/6X10CC	13.0 mm	145.0 mm

