



MASTER SON-T PIA Plus

MASTER SON-T PIA Plus 600W/220 E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Lumen Maintenance 5000 h (Nom)	
Cap-Base	E40 [E40]	Lumen Maintenance 5000 h (Nom)	90 %
Operating Position	UNIVERSAL [Any or Universal (U)]	Chromaticity Coordinate X (Nom)	0.530
Life to 5% Failures (Nom)	12000 h	Chromaticity Coordinate Y (Nom)	0.428
Life To 10% Failures (Nom)	15000 h	Correlated Color Temperature (Nom)	2000 K
Life to 20% Failures (Nom)	20000 h	Luminous Efficacy (rated) (Nom)	149 lm/W
Life to 50% Failures (Nom)	30000 h	Color Rendering Index (Max)	25
ANSI Code HID	-	Ratio Scotopic/Photopic Lumens	0.60
System Description	External Ignitor	Operating and electrical	
Light technical		Lamp supply voltage	230 V [230]
Color Code	220 [CCT of 2000K]	Power (Nom)	603 W
Luminous Flux (Rated) (Nom)	90000 lm	Lamp Current (EM) (Nom)	5.8 A
Lumen Maintenance 2000 h (Min)	85 %	Ignition Supply Voltage (Max)	198 V
Lumen Maintenance 2000 h (Nom)	96 %	Ignition Peak Voltage (Max)	3500 V
Lumen Maintenance 20000 h	77 %	Re-Ignition Time (Min) (Max)	60 s
Lumen Maintenance 5000 h (Min)	80 %	Ignition Time (Max)	10 s
		Voltage (Max)	125 V

MASTER SON-T PIA Plus

Voltage (Min)	95 V
Voltage (Nom)	110 V

Controls and dimming

Dimmable	No
Run-Up Time 90% (Max)	5 min

Mechanical and housing

Bulb Finish	Clear
Cap-Base Information	-
Bulb Shape	T46 [T 46mm]

Approval and application

Mercury (Hg) Content (Nom)	18.9 mg
Energy Consumption kWh/1000 h	663 kWh


Luminaire design requirements

Bulb Temperature (Max)	450 °C
Cap-Base Temperature (Max)	250 °C

Product data

Full product code	871150019742915
Order product name	MASTER SON-T PIA Plus 600W/220 E40 1SL/12
EAN/UPC - Product	8711500197429
Order code	928158409227
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928158409227
Net Weight (Piece)	0.177 kg
ILCOS Code	ST-600-H/S-E40


Dimensional drawing




Product	D (max)	O	L	C (max)
MASTER SON-T PIA Plus 600W/220 E40 1SL/12	47 mm	126 mm	174.2 mm	279 mm

MASTER SON-T PIA Plus 600W/220 E40 1SL/12

Photometric data




LDLD_SON-TPIA-Light distribution diagram



LDPB_SON-TPIA_0014-Spectral power distribution B/W


MASTER SON-T PIA Plus

Photometric data




LDPO_SON-TPIA_0014-Spectral power distribution Colour


Lifetime




LDLE_SON-TPIA_0004-Life expectancy diagram



LDLE_SON-TPIA_0003-Life expectancy diagram



LDLE_SON-TPIA_600W-Life expectancy diagram



LDLM_SON-TPIA_600W-Lumen maintenance diagram

MASTER SON-T PIA Plus

