



# Architectural MSD

## MSD 700.1CT/3

The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent color rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General information		Operating and electrical	
Cap-Base	G22 [ G22]	Power (Nom)	700 W
Operating Position	UNIVERSAL [ Any or Universal (U)]	Lamp Current (Nom)	11 A
Main Application	Studio/Disco	Ignition Supply Voltage (Min)	207 V
Life to 50% Failures (Nom)	3000 h		
System Description	-		
Light technical		Controls and dimming	
Color Code	- [ Not Specified]	Dimmable	Yes
Luminous Flux (Min)	46800 lm		
Luminous Flux (Nom)	52000 lm	Mechanical and housing	
Chromaticity Coordinate X (Nom)	317	Cap-Base Information	-
Chromaticity Coordinate Y (Nom)	320		
Correlated Color Temperature (Nom)	5900 K	Luminaire design requirements	
Luminous Efficacy (rated) (Nom)	74 lm/W	Bulb Temperature (Max)	600 °C
Color Rendering Index (Nom)	75	Pinch Temperature (Max)	350 °C
Product data			
Full product code	872790091129900		
Order product name	MSD 700.1CT/3		

## Architectural MSD

EAN/UPC - Product	8727900911299
Order code	928170405114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3

Material Nr. (12NC)	928170405114
Net Weight (Piece)	0.147 kg

### Dimensional drawing



MSD 700.1CT/3

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD	40 mm	10.0	84 mm	86 mm	85	175 mm	54 mm	53	52 mm
700.1CT/3		mm			mm			mm	

### Photometric data

