



MSR Gold™ FastFit

MSR Gold™ 1200 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Operating and electrical	
Cap-Base	PGJX50 [PGJX50]	Power (Nom)	1200 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	15 A
Main Application	Entertainment	Ignition Supply Voltage (Min)	198 V
Life to 50% Failures (Nom)	750 h		
System Description	FastFit		
Light technical			
Color Code	- [Not Specified]		
Luminous Flux (Min)	79500 lm		
Luminous Flux (Nom)	95000 lm		
Chromaticity Coordinate X (Nom)	318		
Chromaticity Coordinate Y (Nom)	327		
Correlated Color Temperature (Nom)	6000 K		
Luminous Efficacy (rated) (Nom)	80 lm/W		
Color Rendering Index (Nom)	80		

MSR Gold™ FastFit

Controls and dimming

Dimmable	Yes
----------	-----

Mechanical and housing

Cap-Base Information	PGJX50
----------------------	--------

Luminaire design requirements

Bulb Temperature (Max)	950 °C
Pinch Temperature (Max)	500 °C

Product data

Full product code	871829122129600
-------------------	-----------------

Order product name	MSR Gold™ 1200 FastFit 1CT/4
--------------------	------------------------------

EAN/UPC - Product	8718291221296
-------------------	---------------

Order code	928175005115
------------	--------------


Numerator - Quantity Per Pack	1
-------------------------------	---

Numerator - Packs per outer box	4
---------------------------------	---

Material Nr. (12NC)	928175005115
---------------------	--------------

Net Weight (Piece)	0.147 kg
--------------------	----------

Dimensional drawing



MSR Gold™ 1200 FastFit 1CT/4

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 1200 FastFit 1CT/4	26.1 mm	5.5 mm	64 mm	66 mm	65 mm	128 mm	50 mm

