



# Aluline 37/56

Aluline 20W 12V R37 6D CL 1CT

Low-voltage halogen burner in a lightweight, high-gloss anodised aluminium reflector giving a white halogen light

## Product data

### • General Characteristics

Philips Code	6433
ANSI Code Halogen	GBD
Cap-Base	BA15d
Cap-Base Information	19
Bulb	R37 [R 37mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	2000 hr

### • Electrical Characteristics

Lamp Wattage	20 W
Lamp Wattage Technical	20.0 W
Voltage	12 V
Lamp Current	1.67 A
Dimmable	Yes

### • Light Technical Characteristics

Beam Angle	6 D
Beam Angle Technical	6 D
Luminous Intensity	6400 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

### • Product Dimensions

Overall Length C	41 (max) mm
Diameter D	38 (max) mm

### • Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	250 (max) C


### • Product Data

Order code	923882717125
Full product code	923882717125
Full product name	Aluline 20W 12V R37 6D CL 1CT
Order product name	Alu 20W 12V R37 6D CL 1CT/10X5F
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500401946
Bar code on intermediate packing - EAN2	8711500415929
Bar code on outerbox - EAN3	8711500415936
Logistic code(s) - 12NC	923882717125
ILCOS code	HMGI-20-12-B15d-37/6
Net weight per piece	19.100 gr

# PHILIPS

sense and simplicity

Dimensional drawing



Product	C (Max)	D (Max)
Alu 37mm 6433 20W BA15d 12V 6D CL	41	38



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change