



# Aluline 37/56

Aluline 50W 12V R56 10D CL 1CT

Low-voltage halogen burner in a lightweight, high-gloss anodised aluminium reflector giving a white halogen light

## Product data

### • General Characteristics

Philips Code	6438
ANSI Code Halogen	GBJ
Cap-Base	B15 [B15d]
Cap-Base Information	24X17
Bulb	R56 [R 56mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	2000 hr

### • Electrical Characteristics

Lamp Wattage	50 W
Lamp Wattage Technical	50.0 W
Voltage	12 V
Lamp Current	4.17 A
Dimmable	Yes

### • Light Technical Characteristics

Beam Angle	10 D
Beam Angle Technical	10 D
Luminous Intensity	12000 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

### • Product Dimensions

Overall Length C	60 (max) mm
Diameter D	58 (max) mm

### • Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	250 (max) C


### • Product Data

Order code	923883917102
Full product code	923883917102
Full product name	Aluline 50W 12V R56 10D CL 1CT
Order product name	Alu 50W 12V R56 10D CL 1CT/10X5F
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500402004
Bar code on intermediate packing - EAN2	8711500415981
Bar code on outerbox - EAN3	8711500415998
Logistic code(s) - 12NC	923883917102
ILCOS code	HMGI-50-12-B15d-56/10
Net weight per piece	39.200 gr


# PHILIPS

sense and simplicity

## Dimensional drawing



Product	C (Max)	D (Max)
Alu 56mm 6438 50W B15/24X17 12V 10D CL	58	58



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change