



Aluline 37/56

Aluline 50W 12V R56 25D FR 1CT

Low-voltage halogen burner in a lightweight, high-gloss anodised aluminium reflector giving a white halogen light

Product data

• General Characteristics

Philips Code	6439/FR
ANSI Code Halogen	GBK
Cap-Base	B15 [B15d]
Cap-Base Information	na [-]
Bulb	R56 [R 56mm]
Bulb Finish	Frosted
Operating Position	any [Any or Universal (U)]
Life to 50% failures	2000 hr

• Electrical Characteristics

Lamp Wattage	50 W
Lamp Wattage Technical	50.0 W
Voltage	12 V
Lamp Current	4.17 A
Dimmable	Yes

• Light Technical Characteristics

Beam Angle	25 D
Beam Angle Technical	25 D
Luminous Intensity	2000 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

• Product Dimensions

Overall Length C	60 (max) mm
Diameter D	58 (max) mm

• Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	250 (max) C



• Product Data

Order code	924001617101
Full product code	924001617101
Full product name	Aluline 50W 12V R56 25D FR 1CT
Order product name	Alu 50W 12V R56 25D FR 1CT/10X5F
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500409348
Bar code on intermediate packing - EAN2	8711500422217
Bar code on outerbox - EAN3	8711500422224
Logistic code(s) - 12NC	924001617101
ILCOS code	HMGI/F-50-12-B15d-37/22
Net weight per piece	39.200 gr

PHILIPS

sense and simplicity

Dimensional drawing



Product	C (Max)	D (Max)
Alu 56mm 6439/FR 50W B15 12V 25D FR	58	58



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, May 14
data subject to change