

aluPAR 64 1000 W 240 V NSP

aluPAR 64 | Halogen lamps with parabolic aluminum reflector PAR64, with pin base





Product datasheet

Technical data

Electrical data


| Nominal wattage | 1000 W | | |
|-----------------|--------|--|--|
| Nominal voltage | 240 V | | |

Light technical data

| Beam angle | 14 ° ¹) |
|--------------------|-----------|
| Luminous intensity | 297000 cd |
| Color temperature | 3200 K |

 $^{^{1)}}$ Half-value angle 50°

Dimensions & weight



Product line drawing

| Diameter | 204.0 mm |
|----------|----------|
| Length | 203.1 mm |

Lifespan

| Lifespan | 300 h |
|----------|-------|
|----------|-------|

Additional product data

| Base (standard designation) | GX16d | |
|-----------------------------|-------|--|
| Picto Studio | Yes | |

Certificates & standards

| EEI – Energy Label | В |
|--------------------|---|
|--------------------|---|

Product datasheet


Country specific information

| Product code | METEL-Code | SEG-No. | STK number | UK Org |
|---------------|------------|---------|------------|--------|
| 4008321205896 | - | - | 4730022 | - |

Product datasheet

Safety advice

To prevent personal injury or damage to property, aluPAR 56 and aluPAR 64 lamps may only be operated in suitable luminaires designed with suitable mechanisms (grids etc.) to ensure that in the event of a lamp bursting no parts/shards can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.



Burning position

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (height x width x length) | Volume | Gross weight |
|---------------|-------------------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321205896 | aluPAR 64 1000 W 240 V NSP | Folding carton box 1 | 169 mm x 166 mm x 194 mm | 5.44 dm ³ | 654.00 g |
| 4008321205902 | aluPAR 64 1000 W 240 V NSP | Shipping carton box 6 | 355 mm x 210 mm x 510 mm | 38.02 dm³ | 4306.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further information on the aluPAR lamps can be found in the brochure entitled:

"In a class of their own. OSRAM PAR lamps for entertainment lighting: Lighter, brighter, cooler."

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.