

## SIGNION ultra Rx7s / Rx7s-24 / Fc2/18

\* Hot re-ignition possible

\* Good colour rendering

\* Low maintenance costs due to a long service life

\* UV protection

\* Good colour stability for the entire service life

\* For luminaires with protective glass

Article no.	Designation	Base	Ø [mm]	Length [mm]	Burning position	Ignition voltage [kV]	Lamp current [A]	Nominal lamp power [W]	Rated lamp power [W]	Nominal luminous flux [lm]	Rated luminous flux [lm]	Ambient temperature for max. luminous flux [°C]	Rated lamp efficiency [lm/W]	Mercury content [mg]	Colour temperature [K]	Colour temperature [descr.]	Colour rendering index Ra / Colour rendering level	Nominal service life [h]	Weighted energy consumption [kWh/1 000 h]	Energy efficiency class
220304 <sup>3)</sup>	HIT-DE 70 pw RX7s	RX7s	20,0	114,2	p45	4	0,9	70	75,0	6 000	6 000	25°C	80,0	11,5	2 750	warm white	Ra60-69/2B	13 000	83	A
220704	HIT-DE 70 ww RX7s	RX7s	20,0	114,2	p45	4	0,9	70	75,0	6 000	6 000	25°C	80,0	9,6	3 200	warm white	Ra70-79/2A	13 000	83	A
220904 <sup>3)</sup>	HIT-DE 70 bw RX7s	RX7s	20,0	114,2	p45	4	0,9	70	75,0	6 000	6 000	25°C	80,0	9,1	3 500	brillantweiß	Ra70-79/2A	10 000	83	A
220804	HIT-DE 70 nw RX7s	RX7s	20,0	114,2	p45	4	0,9	70	75,0	6 000	6 000	25°C	80,0	9,1	4 200	neutral white	Ra70-79/2A	15 000	83	A
220604	HIT-DE 70 dw RX7s	RX7s	20,0	114,2	p45	4	0,9	70	75,0	5 500	5 500	25°C	73,3	9,5	5 200	daylight white	Ra70-79/2A	13 000	83	A
220204 <sup>3)</sup>	HIT-DE 70 cw RX7s	Rx7s	20,0	114,2	p45	4	0,9	75	75,0	3 100	3 100	25°C	41,3	13,5	8 800	cool white	Ra>90/1A	13 000	83	B
221101 <sup>3)</sup>	HIT-DE 150 pw RX7s	RX7s-24	23,0	132,0	p45	4	1,8	150	150,0	12 000	12 000	25°C	80,0	14,5	2 750	warm white	Ra70-79/2A	13 000	165	A
221404	HIT-DE 150 ww RX7s	RX7s-24	23,0	132,0	p45	4	1,8	150	150,0	12 000	12 000	25°C	80,0	15,5	3 200	warm white	Ra60-69/2B	6 000	165	A
221504	HIT-DE 150 nw RX7s	RX7s-24	23,0	132,0	p45	4	1,8	150	150,0	12 000	12 000	25°C	80,0	14,0	4 200	neutral white	Ra70-79/2A	15 000	165	A
221704	HIT-DE 150 dw RX7s	RX7s-24	23,0	132,0	p45	4	1,8	150	150,0	13 000	13 000	25°C	86,7	12,0	5 200	daylight white	Ra80-89/1B	13 000	165	A
221204 <sup>3)</sup>	HIT-DE 150 cw RX7s	Rx7s-24	23,0	132,0	p45	4	1,8	150	150,0	7 000	7 000	25°C	46,7	16,5	8 800	cool white	Ra>90/1A	13 000	165	B
222204	HIT-DE 250 nw Fc2	Fc2/18	25,0	139,0	p45	4	3,0	250	250,0	20 000	20 000	25°C	80,0	24,5	4 200	neutral white	Ra70-79/2A	15 000	275	A