



# Brilliantline Dichroic

Brilliantline Dichroic 20W GU5.3 12V MR16 24D 1CT

Low-voltage, xenon gas-filled halogen burner with axial filament optically positioned in a dichroic coated glass reflector

## Product data

### • General Characteristics

Philips Code	14611
ANSI Code Halogen	BBF
Cap-Base	GU5.3
Bulb	MR16 [MR 16inch/50mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	4000 hr

### • Electrical Characteristics

Lamp Wattage	20 W
Lamp Wattage Technical	20.0 W
Voltage	12 V
Lamp Current	1.73 A
Dimmable	Yes

### • Light Technical Characteristics

Beam Angle	24 D
Beam Angle Technical	24 D
Luminous Intensity	1800 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

### • Product Dimensions

Overall Length C	46 (max) mm
------------------	-------------

Diameter D	50 (max) mm
------------	-------------



### • Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	250 (max) C

### • Product Data

Order code	924050117101
Full product code	924050117101
Full product name	Brilliantline Dichroic 20W GU5.3 12V MR16 24D 1CT
Order product name	Brilliantline Dichroic 20W GU5.3 12V MR16 24D 1CT
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500424716
Bar code on intermediate packing - EAN2	8711500424723
Bar code on outerbox - EAN3	8711500424785
Logistic code(s) - 12NC	924050117101
ILCOS code	HRGS-20-12-GU5.3-50-24
Net weight per piece	30.000 gr

## Dimensional drawing



Product	C (Max)	D (Max)
DICHRO Pro 14611 20W GU5.3 12V MR16 24D	46	51



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change