



# Brilliantline Dichroic

Brilliantline Dichroic 35W GU4 12V MR11 10D 1CT

Low-voltage, xenon gas-filled halogen burner with axial filament optically positioned in a dichroic coated glass reflector

## Product data

### • General Characteristics

Philips Code	14626
ANSI Code Halogen	FTE
Cap-Base	GU4
Bulb	MR11 [MR 11inch/35mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	4000 hr

### • Electrical Characteristics

Lamp Wattage	35 W
Lamp Wattage Technical	35.0 W
Voltage	12 V
Lamp Current	2.92 A
Dimmable	Yes

### • Light Technical Characteristics

Beam Angle	10 D
Beam Angle Technical	10 D
Luminous Intensity	7000 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

### • Product Dimensions

Overall Length C	40 (max) mm
------------------	-------------

Diameter D	35.3 (max) mm
------------	---------------

### • Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	300 (max) C


### • Product Data

Order code	924051417102
Full product code	924051417102
Full product name	Brilliantline Dichroic 35W GU4 12V MR11 10D 1CT
Order product name	Brilliantline Dichroic 35W GU4 12V MR11 10D 1CT
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500425430
Bar code on intermediate packing - EAN2	8711500425447
Bar code on outerbox - EAN3	8711500425454
Logistic code(s) - 12NC	924051417102
ILCOS code	HRGS-35-12-GU4-35/10
Net weight per piece	14.100 gr

# PHILIPS

sense and simplicity

## Dimensional drawing



Product	C (Max)	D (Max)
DICHRO Pro 14626 35W GU4 12V MR11 10D	40	35.3



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change