

HID-HeavyDuty BSN semi-parallel for SON/CDO/MH/HPI

HID-HeavyDuty BSN 70 L33 230V 50Hz HD1-118

Encapsulated electromagnetic copper/iron ballasts for use with an external semi-parallel ignitor for CDM, CDO, MH, HPI (Plus) and SON lamps (no ignitor needed for SON-I lamps)



HID-HeavyDuty BSN semi-parallel for SON/CDO/MH/HPI

Product data

General Characteristics

Rated Number of 1 piece
Lamps
Rated Ballast-Lamp 70
Power
Rated Lamptype SON/CDO

Application code L33
Line Voltage 230 V
Line Frequency 50 Hz
Design HD1-118

Operating Characteristics

Input current with 0.45 A PF-correct. Input current w/o PF-0.98 A correct. Mains voltage safety -10%/+10% (AC) Mains voltage -8%/+6% performance (AC) 0.87 -PowerFactor 100% output power PowerFactor w/o PF 0.35 compens. Power losses gear 11.0 W


• Wiring Characteristics

Connector type Screw
Striplength 7.0 mm
Wcs Ballast contacts 0.70-6.00 mm2

• Temperature Characteristics

Active temperature No protection

Dimensional drawing





T-storage -30 (min), 130 (max) C T-winding maximum 130 (max) C

55 C

(tw)

Delta-T normal conditions

• Approval & Application Chars

CE marking Yes ENEC certificate Yes

• Product Dimensions

Length A1 118.0 mm
Fixing Hole Distance
Length A2
Width B1 65.0 mm
Height C1 53.0 mm
Fixing Hole Diameter D1

• Product Data

Order code 913655010426 Full product code 913655010426 BSN 70 L33 230V 50Hz HD1-118 Full product name Order product name BSN 70 L33 230V 50Hz HD1-118 Pieces per pack Packing configuration 6 Packs per outerbox 8711500920096 Bar code on pack -EAN1 Bar code on 8711500061980 outerbox - EAN3 913655010426 Logistic code(s) -12NC Net weight per piece 1.280 kg

Product	A1 (Norm)	A2 (Norm)	B1 (Norm)	C1 (Norm)	D1 (Norm)	
BSN 70 L33 230V 50Hz HD1-118	118.0	103.0	65.0	53.0	6.2	



© 2011 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.