



# Brilliantline Alu

Brilliantline Alu 20W GU5.3 12V MR16 36D 1CT

Low voltage, xenon gas filled halogen burner with axial filament optically positioned in a aluminum coated glass reflector

## Product data

### • General Characteristics

Philips Code	14715
ANSI Code Halogen	BAB
Cap-Base	GU5.3
Bulb	MR16 [MR 16inch/50mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	4000 hr

### • Electrical Characteristics

Lamp Wattage	20 W
Lamp Wattage Technical	20.6 W
Voltage	12 V
Lamp Current	1.72 A
Dimmable	Yes

### • Light Technical Characteristics

Beam Angle	36 D
Beam Angle Technical	36 D
Luminous Intensity	700 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

### • Product Dimensions

Overall Length C	46 (max) mm
------------------	-------------

Diameter D	51 (max) mm
------------	-------------

### • Luminaire Design Requirements

Cap-Base Temperature	350 (max) C
Bulb Temperature	250 (max) C



### • Product Data

Order code	924057217101
Full product code	924057217101
Full product name	Brilliantline Alu 20W GU5.3 12V MR16 36D 1CT
Order product name	BrillAI 20W GU5.3 12V MR16 36D 1CT/10X5F
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500430724
Bar code on intermediate packing - EAN2	8711500430731
Bar code on outerbox - EAN3	8711500430748
Logistic code(s) - 12NC	924057217101
ILCOS code	HAGS-20-12-GU5.3-50/36
Net weight per piece	30.000 gr

# PHILIPS

sense and simplicity

## Dimensional drawing



Product	C (Max)	D (Max)
ALU 14715 20W GU5.3 12V MR16 36D	46	51



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change